NPS ENGINES

Break In Procedure & Recommended Accessories.

GSXR - 600, 750, 1000 Series **R** Engine



NIAGARA POWERSPORTS 2268 Youngstown-Wilson Rd. Ransomville, New York 14131 United States of America npsengines@gmail.com npsracing.com 716-791-4325

Y

Recommended	Accessory	Manufacturer	Part #	<u>Qty</u> .
Accessories, Fluids and Fuels.	Break-In Engine Oil	Maxima 10w30 Break-In	NPS-BIO-1030	4
	Race Engine Oil	Maxima Extra 10W60	NPS-EX-1060	4
	Oil Filter	HiFlo	NPSHF-138r	1
	Spark Plugs	NGK	NPS-CR10e	4
	Oil Pan	Pro	NPS-BOP-G6	1
	Crankcase Breather Kit	NPS Inc.	NPS-CCB-1	1
	Fuels	VP	U4, MR12	5
Recommended Start Up Procedure.	 Set spark gap (.030") ; 	and install the recommended	spark plugs.	
	 Enable ignition and fue Start engine and let it Turn off engine and let Check engine oil and a 	elivery system and purge air el systems. run for 1 minute. it sit for 3 minutes. all fluid levels. run to 160 °F at various throt nutes.		
ractice Session and Race.	 Start engine, while using various RPM's bring temps to 185°F and turn engine Change engine oil to recommended <u>Race Oil.</u> Check and set all fluid levels. 			
	 Keep engine below 12 Return to pits. Turn off engine and let Check all fluids and let Restart engine and brit Check all fluids and let 	vels. ng up to 185°F then turn the vels. up to 180°F before entering	5 practice laps. engine off.	acing.

Not following these recommendations and procedures can seriously effect your engines integrity and optimum performance.

NPS Inc. All Rights Reserved 1995-2020 Property of NIAGARA POWERSPORTS INC. Do Not Copy, Redistribute or Reproduce.